



ELECTRIC VEHICLES

NATIONAL SALES & SERVICE

4532 U. S. HWY. 27 SOUTH /P. O. BOX 1963 / SEBRING, FLORIDA 33870 / PHONE (813) 385-5116

CARE & MAINTENANCE OF THE CITICAR'S ACRYLIC ENAMEL FINISH

WASH

Keep the surfaces clean with clean water and mild detergent, such as Tide. Wash only in the shade - sunlight will cause streaking. Rinse well with clean water. Dry completely before exposing to sunlight.

WAX

Under normal conditions, do not wax the acrylic enamel surface until the CitiCar is six (6) months old. Use any normal automotive cleaner, but do not use any waxes or cleaner-waxes which contain silicone. Pure Carnauba wax, such as "CarGroom" is best.

SURFACE SCRATCHES AND ABRASIONS

Minor scratches may be removed after the CitiCar is six (6) months old with a rubbing compound which breathes, such as "DuPont #7". Do not wheel compound.

For major scratches, the CitiCar must be one (1) year old. At this time, you may wheel compound.

GREASE AND STAIN REMOVAL

After the CitiCar is six (6) months old, use any automotive tar and grease remover.

EXPOSURE TO HEAVY INDUSTRIAL CHEMICAL FALL-OUT

Delicate cleaning and waxing may be done after the CitiCar is three (3) months old. This must be done with a light touch application and with extreme caution.